

1300A

Project _____

QTY _____

Type _____



WEIGHT = 26.0 LBS.
 E.P.A. = 1.74 SQ. FT.
 TENON SIZE = 3" DIA. X 3" LONG

ORDERING INFORMATION

EXAMPLE: 29-35-T5-A-HSS-6005

To specify a fixture choose the **boldface** catalog nomenclature that best suits your needs and write it on the appropriate line.

1300A -

Wattage	Color Temp.	Optics	Lens Material	Accessories	Finish RAL#
29 29 Watts	27 2700K	T2 Type II	CP Clear Polycarbonate	N None	9005 Black
46 46 Watts	35 3500K	T3 Type III	FP Frosted Polycarb.	PEC Photo Elec.	6005 Moss Green
78 78 Watts	40 4000K	T5 Type v	PP Prismatic Polycarb.	Control	6012 Dark Green
117 117 Watts	50 5000K		SA Seeded Acrylic	HSS House Side	OR- Specify RAL#
			WP White Polycarbonate	Shield	
			NL No Lens		

1300A

PERFORMANCE DATA

SPECIFICATIONS

LIGHT EMITTING DIODE (LED) ASSEMBLY SHALL BE A SEALED UNIT WITH AN ALUMINUM HEAT SINK, AND IS A IP66 RATED SYSTEM

LUMINAIRE MEETS UL-1598 LISTING. FIXTURE IS SUITABLE FOR WET LOCATIONS.

LUMINAIRE SHALL ACCEPT 120-277, 50/60 Hz INPUT VOLTAGE, AND HAS INTERNAL SURGE PROTECTION.

DRIVER SHALL BE U.L. RECOGNIZED AND HAVE A 0-10 VOLT DIMMING INTERFACE.

LUMINAIRE FINISH SHALL BE A TGIC POLYESTER POWDER COAT FINISH.

WATTAGE	COLOR TEMP	LUMENS	LUMENS/WATT
29	2700K	2700	90
29	3500K	2700	90
29	4000K	3600	120
29	5000K	3600	120
46	2700K	3450	80
46	3500K	3910	85
46	4000K	5014	109
46	5000K	5290	115
78	2700K	6000	80
78	3500K	6800	85
78	4000K	8720	109
78	5000K	9200	115
117	2700K	9000	80
117	3500K	10,200	85
117	4000K	13,080	109
117	5000K	13,920	115

