

3100A



Project _____

QTY _____

Type _____

WEIGHT = 30.0 LBS.
 E.P.A. = 2.10 SQ. FT.
 TENON SIZE = 3" DIA. X 3" LONG

ORDERING INFORMATION

EXAMPLE: 29-35-T5-A-HSS-6005

To specify a fixture choose the **boldface** catalog nomenclature that best suits your needs and write it on the appropriate line.

3100A -

| Wattage | Color Temp. | Optics | Lens Material | Accessories | Finish RAL# |
|----------------------|-----------------|--------------------|-------------------------------|------------------------|-------------------------|
| 29 29 Watts | 27 2700K | T2 Type II | CP Clear Polycarbonate | N None | 9005 Black |
| 46 46 Watts | 35 3500K | T3 Type III | FP Frosted Polycarb. | PEC Photo Elec. | 6005 Moss Green |
| 78 78 Watts | 40 4000K | T5 Type v | PP Prismatic Polycarb. | Control | 6012 Dark Green |
| 117 117 Watts | 50 5000K | | SA Seeded Acrylic | HSS House Side | OR- Specify RAL# |
| | | | WP White Polycarbonate | Shield | |
| | | | NL No Lens | | |

3100A

PERFORMANCE DATA

SPECIFICATIONS

LIGHT EMITTING DIODE (LED) ASSEMBLY SHALL BE A SEALED UNIT WITH AN ALUMINUM HEAT SINK, AND IS A IP66 RATED SYSTEM

LUMINAIRE MEETS UL-1598 LISTING. FIXTURE IS SUITABLE FOR WET LOCATIONS.

LUMINAIRE SHALL ACCEPT 120-277, 50/60 Hz INPUT VOLTAGE, AND HAS INTERNAL SURGE PROTECTION.

DRIVER SHALL BE U.L. RECOGNIZED AND HAVE A 0-10 VOLT DIMMING INTERFACE.

LUMINAIRE FINISH SHALL BE A TGIC POLYESTER POWDER COAT FINISH.

| WATTAGE | COLOR TEMP | LUMENS | LUMENS/WATT |
|---------|------------|--------|-------------|
| 29 | 2700K | 2700 | 90 |
| 29 | 3500K | 2700 | 90 |
| 29 | 4000K | 3600 | 120 |
| 29 | 5000K | 3600 | 120 |
| 46 | 2700K | 3450 | 80 |
| 46 | 3500K | 3910 | 85 |
| 46 | 4000K | 5014 | 109 |
| 46 | 5000K | 5290 | 115 |
| 78 | 2700K | 6000 | 80 |
| 78 | 3500K | 6800 | 85 |
| 78 | 4000K | 8720 | 109 |
| 78 | 5000K | 9200 | 115 |
| 117 | 2700K | 9000 | 80 |
| 117 | 3500K | 10,200 | 85 |
| 117 | 4000K | 13,080 | 109 |
| 117 | 5000K | 13,920 | 115 |

