

# 3300A



Project \_\_\_\_\_

QTY \_\_\_\_\_

Type \_\_\_\_\_

WEIGHT = 21.8 LBS.  
 E.P.A. = 2.20 SQ. FT.  
 TENON SIZE = 3" DIA. X 3" LONG

## ORDERING INFORMATION

EXAMPLE: 29-35-T5-A-HSS-6005

To specify a fixture choose the **boldface** catalog nomenclature that best suits your needs and write it on the appropriate line.

## 3300A -

Wattage	Color Temp.	Optics	Lens Material	Accessories	Finish RAL#
<b>29</b> 29 Watts	<b>27</b> 2700K	<b>T2</b> Type II	<b>CP</b> Clear Polycarbonate	<b>N</b> None	<b>9005</b> Black
<b>46</b> 46 Watts	<b>35</b> 3500K	<b>T3</b> Type III	<b>FP</b> Frosted Polycarb.	<b>PEC</b> Photo Elec. Control	<b>6005</b> Moss Green
<b>78</b> 78 Watts	<b>40</b> 4000K	<b>T5</b> Type v	<b>PP</b> Prismatic Polycarb.	<b>HSS</b> House Side Shield	<b>6012</b> Dark Green
	<b>50</b> 5000K		<b>WP</b> White Polycarb.		<b>OR-</b> Specify RAL#
			<b>NL</b> No Lens		

3300A

## PERFORMANCE DATA

## SPECIFICATIONS

LIGHT EMITTING DIODE (LED) ASSEMBLY SHALL BE A SEALED UNIT WITH AN ALUMINUM HEAT SINK, AND IS A IP66 RATED SYSTEM

LUMINAIRE MEETS UL-1598 LISTING. FIXTURE IS SUITABLE FOR WET LOCATIONS.

LUMINAIRE SHALL ACCEPT 120-277, 50/60 Hz INPUT VOLTAGE, AND HAS INTERNAL SURGE PROTECTION.

DRIVER SHALL BE U.L. RECOGNIZED AND HAVE A 0-10 VOLT DIMMING INTERFACE.

LUMINAIRE FINISH SHALL BE A TGIC POLYESTER POWDER COAT FINISH.

WATTAGE	COLOR TEMP	LUMENS	LUMENS/WATT
29	2700K	2700	90
29	3500K	2700	90
29	4000K	3600	120
29	5000K	3600	120
46	2700K	3450	80
46	3500K	3910	85
46	4000K	5014	109
46	5000K	5290	115
78	2700K	6000	80
78	3500K	6800	85
78	4000K	8720	109
78	5000K	9200	115

