

3900A



Project _____

QTY _____

Type _____

WEIGHT = 28.0 LBS.
 E.P.A. = 2.15 SQ. FT.
 TENON SIZE = 3" DIA. X 3" LONG

EXAMPLE: 29-35-T5-A-HSS-6005

ORDERING INFORMATION

To specify a fixture choose the **boldface** catalog nomenclature that best suits your needs and write it on the appropriate line.

3900A -

Wattage	Color Temp.	Optics	Lens Material	Accessories	Finish RAL#
31 31 Watts	27 2700K	T5 Type v	FP Frosted Polycarb.	N None	9005 Black
42 42 Watts	35 3500K		PP Prismatic Polycarb.	PEC Photo Elec.	6005 Moss Green
52 52 Watts	40 4000K		SA Seeded Acrylic	Control	6012 Dark Green
62 62 Watts	50 5000K		WP White Polycarbonate	HSS House Side Shield	OR- Specify RAL#
73 73 Watts					
83 83 Watts					
94 94 Watts					
104 104 Watts					
114 114 Watts					

PERFORMANCE DATA

WATTAGE	COLOR TEMP	LUMENS	LUMENS/WATT
31	2700K	2720	80
31	3500K	2890	85
31	4000K	3706	109
31	5000K	3910	115
42	2700K	3375	80
42	3500K	3825	85
42	4000K	4905	109
42	5000K	5175	115
52	2700K	3975	80
52	3500K	4505	85
52	4000K	5777	109
52	5000K	6905	115
62	2700K	4800	80
62	3500K	5440	85
62	4000K	6976	109
62	5000K	7360	115
73	2700K	5475	80
73	3500K	6205	85
73	4000K	7957	109
73	5000K	8395	115
83	2700K	6300	80
83	3500K	7140	85
83	4000K	9156	109
83	5000K	9660	115
94	2700K	6975	80
94	3500K	7905	85
94	4000K	10,137	109
94	5000K	10,695	115
104	2700K	7725	80
104	3500K	8755	85
104	4000K	11,227	109
104	5000K	11,845	118
114	2700K	8559	80
114	3500K	9690	85
114	4000K	12,426	109
114	5000K	13,110	115

3900A

SPECIFICATIONS

LIGHT EMITTING DIODE (LED) ASSEMBLY SHALL BE A SEALED UNIT WITH AN ALUMINUM HEAT SINK, AND IS A IP66 RATED SYSTEM

LUMINAIRE MEETS UL-1598 LISTING. FIXTURE IS SUITABLE FOR WET LOCATIONS.

LUMINAIRE SHALL ACCEPT 120-277, 50/60 Hz INPUT VOLTAGE, AND HAS INTERNAL SURGE PROTECTION.

DRIVER SHALL BE U.L. RECOGNIZED AND HAVE A 0-10 VOLT DIMMING INTERFACE.

LUMINAIRE FINISH SHALL BE A TGIC POLYESTER POWDER COAT FINISH.



• 29579 Awbrey Lane • Eugene, Oregon 97402
 tel: 541.688.7741 • fax: 541.461.0951 • 1.800.341.1444
 • www.visco-light.com