

Project \_\_\_\_\_

QTY \_\_\_\_\_

Type \_\_\_\_\_

# 4200M



WEIGHT = 19.0 LBS.  
 E.P.A. = .70 SQ. FT.  
 TENON SIZE = 2" PIPE

## ORDERING INFORMATION

EXAMPLE: 29-35-T5-A-HSS-6005

To specify a fixture choose the **boldface** catalog nomenclature that best suits your needs and write it on the appropriate line.

## 4200M -

Wattage	Color Temp.	Optics	Lens Material	Accessories	Finish RAL#
<b>49</b> 49 Watts	<b>30</b> 3000K	<b>T3</b> Type III	<b>AC</b> Acrylic	<b>PEC</b> Photo Elec.	<b>9005</b> Black
<b>98</b> 98 Watts	<b>40</b> 4000K	<b>T5</b> Type V	<b>CP</b> Clear Polycarbonate	Control	<b>6005</b> Moss Green
<b>147</b> 147 Watts	<b>50</b> 5000K			<b>N</b> None	<b>6012</b> Dark Green
					<b>OR-</b> Specify RAL#

4200M

## PERFORMANCE DATA

## SPECIFICATIONS

LIGHT EMITTING DIODE (LED) ASSEMBLY SHALL BE A SEALED UNIT WITH AN ALUMINUM HEAT SINK, AND IS A IP66 RATED SYSTEM

LUMINAIRE MEETS UL-1598 LISTING. FIXTURE IS SUITABLE FOR WET LOCATIONS.

LUMINAIRE SHALL ACCEPT 120-277, 50/60 Hz INPUT VOLTAGE, AND HAS INTERNAL SURGE PROTECTION.

DRIVER SHALL BE U.L. RECOGNIZED AND HAVE A 0-10 VOLT DIMMING INTERFACE.

LUMINAIRE FINISH SHALL BE A TGIC POLYESTER POWDER COAT FINISH.

WATTAGE	COLOR TEMP	LUMENS	LUMENS/WATT
49	3000K	6300	128
49	4000K	6300	128
49	5000K	6300	128
98	3000K	12,600	128
98	4000K	12,600	128
98	5000K	12,600	128
147	3000K	18,900	128
147	4000K	18,900	128
147	5000K	18,900	128

